



משואות מצוקה וביות לווניות EPIRB / PLB



Beacon Name Model #	GlobalFix™ iPRO Cat I /Cat II RLB-36	GlobalFix™ PRO Cat I /Cat II RLB-37	Satellite3™ Cat I /Cat II RLB-38	AquaLink™ PLB-350B	AquaLink™ View PLB-350Bc	ResQLink™/RsQLink™+ PLB-375	שם מודל
ACR Product #	2846.0/2848.0	2842/2844	2874/2875	2882	2884	2880/2881	קטלוגי
Frequency	406.037 MHz	406.037 MHz	406.037 MHz	406.037 MHz	406.037 MHz	406.037 MHz	תדר משואה
Frequency	121.5 MHz Homing	121.5 MHz Homing	121.5 MHz Homing	121.5 MHz Homing	121.5 MHz Homing	121.5 MHz Homing	תדר ביوت מסוקים
GPS	Internal and Optical Interface (NMEA)	YES - Internal	GPS Interface (NMEA) Optional	Internal 66 Channel Receiver	Internal 66 Channel Receiver	Internal 66 Channel Receiver	GPS
Location Accuracy	.05 nm (110 yards)	.05 nm (110 yards)	2.3 nm or .05 nm with GPS Interface	.05 nm (110 yards)	.05 nm (110 yards)	.05 nm (110 yards)	דיוק מיקום
Size: in (cm) Weight: lbs (g)	15.3 X 4.2 X 3.6 in (38.9 X 10.7 X 9.1 cm) 1.32 lbs (600 g)	15.3 X 4.2 X 3.6 in (38.9 X 10.7 X 9.1 cm) 1.31 lbs (595 g)	15.3 X 4.2 X 3.6 in (38.9 X 10.7 X 9.1 cm) 1.31 lbs (595 g)	2.25 X 5.88 X 1.49 in (5.72 X 14.9 X 3.78 cm) 9.2 oz. (260 g)	2.25 X 5.88 X 1.49 in (5.72 X 14.9 X 3.78 cm) 9.2 oz. (260 g)	(3.3 x 4.8 x 9.9 cm) (4.1 x 4.8 x 11.4 cm) (130g) (153g)	מידות משקל
Notification Time	2-15 min.	2-15 min.	2-15 min. with GPS Up to 1 hr. non GPS	2-15 min.	2-15 min.	2-15 min.	זמן התראה
Deployment	Automatic (Category I) Manual (Category II)	Automatic (Category I) Manual (Category II)	Automatic (Category I) Manual (Category II)	Manual Only	Manual Only	Manual Only	שחרור
Activation	Water or Manual	Water or Manual	Water or Manual	Manual	Manual	Manual	הפעלה
Bracket, Cat II	Low Pro 3	Low Pro 3	QuickDraw	-	-	-	תושבת CAT II
Minimum Required Battery Life	48 hours @ -4°F (-20°C)	48 hours @ -4°F (-20°C)	48 hours @ -4°F (-20°C)	24 hours @ -4°F (-20°C)	24 hours @ -4°F (-20°C)	24 hours @ -4°F (-20°C)	מינימום זמן סוללה נדרש
Typical Battery Life	72 hours @ -4°F (-20°C)	72 hours @ -4°F (-20°C)	72 hours @ -4°F (-20°C)	35 hours @ -4°F (-20°C)	30 hours @ -4°F (-20°C)	30 hours @ -4°F (-20°C)	זמן סוללה אופייני
Digital Display	Yes - Full	No	No	No	Yes - Full	No	תצוגה דיגיטלית
Waterproof	To 33 ft. (10 m)	To 33 ft. (10 m)	To 33 ft. (10 m)	To 16.5 ft. (5 m)	To 16.5 ft. (5 m)	To 16.5 ft. (5 m)	הגנה מחדירת מים
Buoyant	Yes	Yes	Yes	Yes	Yes	Needs pouch / Yes	ציפה
Batteries/shipping	Lithium non-Hazmat	Lithium non-Hazmat	Lithium non-Hazmat	Lithium non-Hazmat	Lithium non-Hazmat	Lithium non-Hazmat	סוללות ומשלוח
Strobe Light	Yes	Yes	Yes	Yes	Yes	Yes	נצנץ מצוקה לבן
Self Test + LED	Yes	Yes	Yes	Yes	Yes	Yes	בדיקה עצמית וחיווי LED
GPS Location Tests	Yes	Yes	No	Yes, Satellite Detectable	Yes, Satellite Detectable	Yes, Satellite Detectable	בדיקת מיקום GPS
406Link.com	I'm OK (only)	I'm OK (only)	I'm OK (only)	I'm OK with GPS	I'm OK with GPS	I'm OK with GPS	שירות *406Link.com



Subsidiary of:
EFFECT Group
Tel: 03-613-2280



5 - היכן שהשירות קיים
5 שנות אחריות או בהתאם לאחריות היצרן - הנמוך מביניהם.
החברה רשאית לבצע שינויים במפרט ובמחיר בכל עת.

המחירים בתוקף מ 1.1.2011 ועד להודעה חדשה.
ט.ל.ח.